

Product description

Discount set consisting of 1 lashing strap and 1 set of 2 high-quality aluminum ramps. Very suitable for transporting vehicles such as; golf cart, quad, small car, lawnmower, carriage or e.g. mini tractors. Easy to move due to the light weight, 7.5 kg each. The anti-slip profile prevents slipping.

Maximum load capacity 1000 kg. Ideal angle 21 degrees. Ideal trailer height 86 cm. The load capacity depends on various factors and decreases if:

- the drive-on height of the ramp decreases.
- the axle distance is less than 1250 mm.
- the road contact is less than 100 x 150 mm.
- the weight distribution is different than 2/3 on one axle and 1/3 on the other axle.
- drive-up speeds are above 5 km/h.
- there are vibrations when accelerating or braking abruptly.

The ramps must be fully raised with the flat part attached to the bottom of the trailer so that it cannot slide. When calculating the load capacity, the dynamic load has been taken into account and the safety factor 2 has been used with a weight of more than 500 kg. Calculate the weight as follows; total weight of the vehicle + fuel (1 liter is 1 kg) + weight of 1 person + weight of accessories.

* not suitable for tracked vehicles!

Specifications

Article arrangement: New Version: aluminium 250 cm (pair) with 1 free cargo lash Top: driving area of anti slip profile Width (mm): 260 Loading capacity (kg): 1000 Options: NOT suitable for caterpillar Batch (items): 2 Min Height (mm): 750 EAN Code (Gtin) 8719424120486 Type: access ramp straight Material: aluminium Length (mm): 2498 Height (mm): 75 Weight (kg) 7.5 Type number: 86R-S Drive width: 260 Max Height (mm): 900







KRUIZINGA.FR[®] Stockage et ressources de transport





Technical information Productnumber: 86R25-75-S







KRUIZINGA.FR[®] Stockage et ressources de transport

