


Image not found or type unknown



Technical information

Productnumber : 705S422P1650



Product description

Sturdy 4-sided roll container with a steel rolling base fitted with smooth polyamide wheels. The roll container has a double door at the front. Fast assembly and disassembly of the insert gates. 2 nylon lashing straps are supplied as standard with each roll container. Extra option to provide the roll container with a maximum of 5 (wooden, steel or plastic) floors. Very suitable for the distribution of products to and from shops and internal transport.

Specifications

Article arrangement: New

Version: input gates + 2 nylon tensioning belts

Walls: mesh

Wheels front: 2 castor wheels nylon, 108 mm

Wheels back: 2 fixed wheels nylon 108 mm

Colour: colorless

Length (mm): 800

Width (mm): 710

Height (mm): 1830

Loading capacity (kg): 500

Additional specifications: nylon wheels

Type: 4 sides double door

Material: steel

Floor: steel

Subgroup: 4-Sides

Shelves: excl. shelves

Surface treatment: electro-galvanized

Internal length (mm): 750

Internal width (mm): 660

Internal height (mm): 1650

Type number: 704S02

EAN Code (Gtin) 8719424143829

Scan the QR code for more information



KRUIZINGA.NL®
Opslag- en transportmiddelen

KRUIZINGA.DE®
Lager- und Transportmittel

KRUIZINGA.FR®
Stockage et ressources de transport

KRUIZINGA.COM®
Material handling equipment