



Technical information

Productnumber : 75.100.542.260



Product description

Wheel diameter: 252 mm

Wheel width: 85 mm

Conduct: 150 kg

lower type: Rollager

axmm000d_: 20 mm

naaf length: 74 mm

Walking: polyme

velgenmaterial Advantages: For medium-heavy transport of, for example, shock-sensitive products or on an irregular / unpaved surface. Low noise and vibration damping.

Applications: Versatile use for light transport in eg offices, warehouses, shops and institutions. Low-noise, impact-resistant and vibration-damping. Swivel castor for light duty applications. Less suitable for long-term static use under maximum load.

Suitable surface: Almost any surface, both indoors and outdoors. Uneven surfaces such as clinker bricks, damaged floors and obstacles such as thresholds. Unpaved surfaces.

Suitable environment: Dry and not permanently damp. With weak chemicals.

Specifications

Article arrangement: New

Version: Ø 252 mm

Top: base plate 175x140 mm

Bolt hole: Ø 20 mm

Surface treatment: electro-galvanized

Width (mm): 85

Loading capacity (kg): 150

Type number: 755422

Type: air tire

Material: Pneumatic tyre

Hole centres: 140x105 mm

Colour: colorless

Length (mm): 290

Height (mm): 260

Wheel bearing: roller bearing

EAN Code (Gtin) 8719424013382

Scan the QR code for more information



KRUIZINGA.NL®
Opslag- en transportmiddelen

KRUIZINGA.DE®
Lager- und Transportmittel

KRUIZINGA.FR®
Stockage et ressources de transport

KRUIZINGA.COM®
Material handling equipment

Image not found or type unknown.



Technical information

Productnumber : 75.100.542.260



KRUIZINGA.NL[®]
Opslag- en transportmiddelen

KRUIZINGA.DE[®]
Lager- und Transportmittel

KRUIZINGA.FR[®]
Stockage et ressources de transport

KRUIZINGA.COM[®]
Material handling equipment