


Image not found or type unknown.



## Technical information

**Productnumber : 75.146.612.163**



### Product description

for more information see manual.

**Advantages:** The solid rubber tires have a hardness of 80 ° Shore A and offer good driving characteristics, roll silently, are shock and impact resistant, corrosion resistant and have an average rolling resistance.

**Applications:** Industrial carts, material handling in factories, waste containers, transport containers, metal and chemical companies, roll containers for medium-heavy loads, tool trolleys, warehouse carts. The belt may leave black marks.

**Suitable environment:** Dry and not permanently damp. With mild acids and bases.

### Specifications

Article arrangement: New

Version: Ø 160 mm

Top: base plate 135x110 mm

Bolt hole: Ø 11 mm

Surface treatment: galvanized

Width (mm): 39

Loading capacity (kg): 180

Wheel bearing: roller bearing

EAN Code (Gtin) 8719424013696

Type: castor wheel with brake

Material: standard rubber band

Hole centres: 105x80 mm

Colour: colorless

Length (mm): 160

Height (mm): 190

Weight (kg) 3

Type number: 754661

Scan the QR code for more information



**KRUIZINGA.NL**®  
Opslag- en transportmiddelen

**KRUIZINGA.DE**®  
Lager- und Transportmittel

**KRUIZINGA.FR**®  
Stockage et ressources de transport

**KRUIZINGA.COM**®  
Material handling equipment