

Image not found or type unknown



Technical information

Productnumber : 75.184.782.103K



Product description

for more information see manual.

Advantages: For medium-heavy transport on flat floors. Low rolling resistance. Relatively insensitive to notches and very wear-resistant. Non-marking tyre, low-noise operation, hygienic.

Applications: Industrial trolleys, material handling in factories, waste containers, transport containers, metal and chemical companies, medium-duty rolling containers, tool trolleys, warehouse trolleys.

Suitable surface: Hard and flat such as tiles, cement and coatings.

Suitable environment: Dry and not permanently damp. With alcohol, glycol and many acids, bases and chemicals.

Specifications

Article arrangement: New

Version: Ø 100 mm

Top: base plate 105x85 mm

Bolt hole: Ø 9 mm

Surface treatment: galvanized

Width (mm): 86

Loading capacity (kg): 160

Wheel bearing: ball bearing

EAN Code (Gtin) 8719424014266

Type: castor wheel with brake

Material: elastic rubber band

Hole centres: 80x60 mm

Colour: colorless

Length (mm): 105

Height (mm): 128

Weight (kg) 1

Type number: 758478

Scan the QR code for more information



KRUIZINGA.NL®
Opslag- en transportmiddelen

KRUIZINGA.DE®
Lager- und Transportmittel

KRUIZINGA.FR®
Stockage et ressources de transport

KRUIZINGA.COM®
Material handling equipment