

Image not found or type unknown.



## Technical information

**Productnumber : 75.246.612.120**



### Product description

for more information see manual.

**Advantages:** The solid rubber tires have a hardness of 80 ° Shore A and offer good driving characteristics, roll silently, are shock and impact resistant, corrosion resistant and have an average rolling resistance.

**Applications:** Industrial carts, material handling in factories, waste containers, transport containers, metal and chemical companies, roll containers for medium-heavy loads, tool trolleys, warehouse carts. The belt may leave black marks.

**Suitable environment:** Dry and not permanently damp. With mild acids and bases.

### Specifications

Article arrangement: New

Version: Ø 125 mm

Top: base plate 105x85 mm

Bolt hole: Ø 9 mm

Surface treatment: galvanized

Width (mm): 27

Loading capacity (kg): 100

Type number: 754661

Type: right wheel

Material: standard rubber band

Hole centres: 80x60 mm

Colour: colorless

Length (mm): 125

Height (mm): 155

Wheel bearing: roller bearing

EAN Code (Gtin) 8719424014471

Scan the QR code for more information



**KRUIZINGA.NL®**  
Opslag- en transportmiddelen

**KRUIZINGA.DE®**  
Lager- und Transportmittel

**KRUIZINGA.FR®**  
Stockage et ressources de transport

**KRUIZINGA.COM®**  
Material handling equipment